




EINNOVA
SOLARLINE

Portable Power Station

www.einnova-solarline.com

800 W



BMS protection

Protect batteries from overheating and low temperature short circuits, over-voltage, under-voltage, etc.



11 outputs

There are 11 output ports available, so you don't need to worry about not having enough ports anymore.



LiFePO4 battery

6000+ cycle times at 80% depth.



Uninterrupted Power Supply Function

UPS function can be activated within 10 ms in case of sudden power failure.



Portable

Small size and light weight, easy to lift with one hand.




1 hour fast charge

Solar panels or local grid charging from 0 to 100 percent in just 1 hour.

Rated Power	800W
Capacity	756Wh
Product Weight	6.2KG
Package Weight	7.5KG
Product Dimension	277*250*267mm
Package Dimension	287*260*277mm

AC Charging	AC Mains Input,800W max MPPT
Input	11.5-30V/8A/100W max AC
USB QC3.0	18W*1
TYPE-C	PD20W*2
TYPE-C	PD100W*1
DC5521	12V/3A*2
XT-60 Output	12V/10A
Charge Temperature	0-55°C
Working Temperature	-20-55°C

500 W



BMS protection

Protect batteries from overheating and low temperature short circuits, over-voltage, under-voltage, etc.



11 outputs

There are 11 output ports available, so you don't need to worry about not having enough ports anymore.



LiFePO4 battery

6000+ cycle times at 80% depth.



Uninterrupted Power Supply Function

UPS function can be activated within 10 ms in case of sudden power failure.



Portable

Small size and light weight, easy to lift with one hand.




1 hour fast charge

Solar panels or local grid charging from 0 to 100 percent in just 1 hour.

Rated Power	500W
Capacity	512Wh
Product Weight	6.2KG
Package Weight	7.5KG
Product Dimension	277*250*267mm
Package Dimension	287*260*277mm

AC Charging	AC Mains Input, 500W max MPPT
Input	11.5-30V/8A/100W max AC
USB QC3.0	18W*1
TYPE-C	PD20W*2
TYPE-C	PD100W*1
DC5521	12V/3A*2
XT-60 Output	12V/10A
Charge Temperature	0-55°C
Working Temperature	-20-55°C

500 W



BMS protection

Protect batteries from overheating and low temperature short circuits, over-voltage, under-voltage, etc.



11 outputs

There are 11 output ports available, so you don't need to worry about not having enough ports anymore.



LiFePO4 battery

6000+ cycle times at 80% depth.



Uninterrupted Power Supply Function

UPS function can be activated within 10 ms in case of sudden power failure.



Portable

Small size and light weight, easy to lift with one hand.




1 hour fast charge

Solar panels or local grid charging from 0 to 100 percent in just 2 hour.

Rated Power	500W
Capacity	519Wh
Product Weight	5.5KG
Package Weight	6.2KG
Product Dimension	286*206*174mm
Package Dimension	296*216*184mm

AC Charging	AC Mains Input,500W max
MPPT Input	12-30V
USB QC3.0	18W*2
TYPE-C	Type-C-A(PD 18W)*2
TYPE-C	Type-C-B(PD 60W)81
DC5521	12V/8A*2
XT-60 Output	12V/10A
Charge Temperature	0-55°C
Working Temperature	-20-55°C

300 W



BMS protection

Protect batteries and equipment from overheating and low temperature short circuits, over-voltage, under-voltage, etc.



10 outputs

There are 10 output ports available, so you don't have to worry about not having enough ports anymore.



LiFePO4 battery

6000+ cycle times at 80% depth.



Uninterrupted Power Supply Function

UPS function can be activated within 10 ms in case of sudden power failure.



Portable

Small size and light weight, easy to lift with one hand



2 hours fast charge

Direct grid charging from zero to 100 percent in about 2 hours.

Rated Power	300W
Capacity	307Wh
Product Weight	4.5KG
Package Weight	5.2KG
Product Dimension	215*150*168mm
Package Dimension	225*160*178mm

AC Charging	12v-30v
USB QC3.0	18W*3
TYPE-C	PD18W*1
TYPE-C	PD60W*1
DC5521	12V/5A*2
XT-60 Output	12V/10A
Charge Temperature	0-55°C
Working Temperature	-20-55°C

Einnova Solarline-to be Your Trusted Partner!

THANK YOU!



No. 116 Suo Street, Jianye District, Nanjing,
China



+86-25-8479-2033
+86-138-13088384



emma.wu@einnova-solarline.com
www.einnova-solarline.com

www.einnova-solarline.com

EINNOVA
SOLARLINE